

# Rubber hoses



## Turbo

### Super-light flexible rubber hose

The Turbo hose has been developed for both indoor and outdoor use. The hose weighs 30–40% less than conventional rubber hoses. Turbo hose is oil resistant.

- Extremely low weight.
- Soft and flexible.
- Grinding and welding spatter resistant.
- Working temperature -30°C to +70°C.

Model	Hose inside dia		Hose outside dia mm	Max working pressure <sup>a</sup> bar	Max rec. air flow <sup>b</sup>	Weight per		Ordering no.
	mm	in				20 m coil kg	30 m coil kg	
Turbo 13 20m	13	1/2	19	20	21	3.9	-	9093 0057 91
Turbo 16 20m	16.8	5/8	22.8	20	43	4.8	-	9093 0057 31
Turbo 20 20m	21	5/6	27	20	75	5.4	-	9093 0057 61
Turbo 13 30m	13	1/2	19	20	21	-	5.9	9093 0057 93
Turbo 16 30m	16.8	5/8	22.8	20	43	-	7.2	9093 0057 33
Turbo 20 30m	21	5/6	27	20	75	8.1	-	9093 0057 62

<sup>a</sup> With a safety factor of 3 at 20°C.

<sup>b</sup> The pressure drop will be 0.2 bar on a hose length of 5 m, including 2 nipples and at an inlet pressure of 7 bar.



## Rubair

### Durable reinforced heavy duty rubber hose

Rubair hose is double reinforced to fulfil all general heavy duty demands and is recommended for indoor and outdoor use. Rubair hose is oil resistant.

- Durable.
- Grinding and welding spatter resistant.
- Working temperature -20°C to +80°C.

Model	Hose inside dia		Hose outside dia mm	Max working pressure <sup>a</sup> bar	Max rec. air flow <sup>b</sup>	Weight per 20 m coil	Ordering no.
	mm	in					
RUBAIR 10	10	3/8	16	16	13	3.6	8202 0402 10
RUBAIR 13	12.5	1/2	19.1	16	21	4.7	8202 0403 13
RUBAIR 16	16	5/8	23	16	43	6.1	8202 0404 16
RUBAIR 20	20	3/4	26.6	16	75	7.8	8202 0405 20

<sup>a</sup> With a safety factor of 4 at 20°C.

<sup>b</sup> The pressure drop will be 0.2 bar on a hose length of 5 m, including 2 nipples and at an inlet pressure of 7 bar.